

# Wind Load Report - 6 Paradise Road

## 1. Site & Building Data

Roof Type: Gable Wind Speed (ult): 115 mph **Exposure Category:** В **Enclosure Class:** Open Building Width (W): 18.5 ft. Building Length (L): 20 ft. Eave Height (he): 9 ft. Foundation Height (hf): 0 ft. Roof Pitch: 8 /12 Eave Overhang (OH<sub>e</sub>): 1 ft. Gable Overhang (OH<sub>g</sub>): 1 ft.

### 2. Parameters & Coefficients

Topographic Factor (Kzt): 1.0 .85 Directionality Factor (K<sub>d</sub>): Roof Angle ( $\theta$ ): 33.69 deg. Mean Roof Height (h): 12.08 ft. Ridge Height (h<sub>r</sub>): 15.17 ft. Pos. Internal Pressure (+GCpi): +0.00Neg. Internal Pressure (-GCpi): -0.00

Velocity Pressure Exp. Coeff. (Kh): 0.70 @ z=h Velocity Pressure (qh): 20.16 psf End Zone Width (a): 3.00 ft. Zone 2/2E Dist.: 9.25 ft.

# 3. Design Assumptions and Notes

Code Standard: **ASCE 7-10** Geometry: Regular-Shaped Bldg. Height Class: Low-Rise Building

Notes:

### 4. Design Loads

Top Chord Dead Load: 5 psf Bottom Chord Dead Load: 5 psf Truss/Rafter Spacing: 16 in. o/c


# 4. Design Wind Pressures: MWFRS Envelope Procedure

Load C	Load Case A: Transverse Direction						
Surface	GCpf	Design Pressure (psf) (w/ +GCpi) (w/ -GCpi)					
1	0.56	11.29					
2	0.21	4.23					
3	-0.43	-8.67					
4	-0.37	-7.46					
1E	0.69	13.91					
2E	0.27	5.44					
3E	-0.53	-10.69					
4E	-0.48	-9.68					
2OH	0.21	4.23					
2EOH	0.27	5.44					
3ОН	-0.43	-8.67					
3ЕОН	-0.53	-10.69					
2OH+W	0.21/-0.7	-9.88					
2EOH+W	0.27/-0.7	-8.67					

- a) (+) and (-) signs signify wind pressures acting toward & away from surfaces. b) External Pressure Coefficients linearly interpolated from Fig. 28.4-1 ASCE 7-10. c) Design building for all wind directions, 4 load patterns per load case.
- d) Total horizontal shear shall not be less than that by neglecting roof wind forces.
- e) Min. wind load for enclosed or partially enclosed bldg.: 16 psf wall, 8 psf roof. f) Design pressures are for strength design, multiply by 0.6 for ASD.

Subject	Customer	Location		Job No.
Wind Loads				2024D208
Norman J Abraham, P.E.	NJA Engineering	STRUCTURAL ENGINEERS	This report may not be copied, reproduced or distributed without the written consent of NJA Engineering	Rev.
5/18/2024	941 New Road ph. 7165721140 www.web	osite.com	Copyright © 2024	Page 1

Load Case B: Longitudinal Direction						
C	CC-f	Design Pressure (psf)				
Surface	GCpf	(w/+GCpi) (w/-GCpi)				
1	-0.45	-9.07				
2	-0.69	-13.91				
3	-0.37	-7.46				
4	-0.45	-9.07				
5	0.40	8.06				
6	-0.29	-5.85				
1E	-0.48	-9.68				
2E	-1.07	-21.57				
3E	-0.53	-10.69				
4E	-0.48	-9.68				
5E	0.61	12.30				
6E	-0.43	-8.67				
2OH	-0.69	-13.91				
2EOH	-1.07	-21.57				
3ОН	-0.37	-7.46				
3ЕОН	-0.53	-10.69				
2EOH+W	-1.07/-0.7	-35.69				
3EOH+W	-0.53/-0.7	-24.80				




- a) (+) and (-) signs signify wind pressures acting toward & away from surfaces.
  b) External Pressure Coefficients linearly interpolated from Fig. 28.4-1 ASCE 7-10.
  c) Design building for all wind directions, 4 load patterns per load case.
  d) Total horizontal shear shall not be less than that by neglecting roof wind forces.
  e) Min. wind load for enclosed or partially enclosed bldg.: 16 psf wall, 8 psf roof.
  f) Design pressures are for strength design, multiply by 0.6 for ASD.

Torsional Load Cases							
Surface	Load Case	GCpf	Design Pressure (psf)				
Burrace	Edua Cuse	ССРГ	(w/+GCpi) (w/-GCpi)				
1T	A	-	2.82				
2T	A	-	1.06				
3T	A	-	-2.17				
4T	A	-	-1.86				
5T	В	-	2.02				
6T	В	-	-1.46				



- a) (+) and (-) signs signify wind pressures acting toward & away from surfaces. b) Pressures designated with a "T" are 25% of full design wind pressures. c) Torsional loading shall apply to all 8 load patterns using the figures shown. d) Design pressures are for strength design, multiply by 0.6 for ASD. e) Torsional Design Exceptions. One story bldg. with  $h \leq 30 \, \text{ft},$


Two stories or less framed with light frame construction, Two stories or less with flexible diaphragms.



Wind Loads	Customer	Location		Job No. 2024D208
Norman J Abraham, P.E.	NJA Engineering	STRUCTURAL ENGINEERS	This report may not be copied, reproduced or distributed without the written consent of NJA Engineering	Rev.
5/18/2024	941 New Road ph. 7165721140 www.web	site.com	Copyright © 2024	Page 2

# 5. Wind Load Calculations

### 1.) <u>Lateral Loads - Transverse Direction</u>:




- a) (-) signs signify wind lateral forces acting opposite to the direction of the arrows shown.
- b) Strength design values multiplied by 0.6 to obtain ASD values.

	Wind Base Shear (ASD)							
	Load Case A: Transverse Direction							
Load Case	Load Case Walls (lbs) Roof (lbs) Roof Overhangs (lbs) Total Lateral Load (lbs) R1 (lbs) R2 (lbs)							
Positive Internal Pressure	1091	1026	106	2223	1174	1049		
Negative Internal Pressure	1091	1026	106	2223	1174	1049		
Roof Pressure = 0	1091	0	0	1091	573	518		
Min. Pressures (8 psf, 16 psf)	864	592	130	1586	793	793		

- a) Bottom half of wall neglected in tributary area calculations.
- b) Strength design values multiplied by 0.6 to obtain ASD values.

Subject Wind Loads	Customer	Location	Job No. 2024D208
Norman J Abraham, P.E.	NJA Engineering	This report may not copied, reproduced distributed without it written consent of N. Faulerung varieties.	-
5/18/2024	941 New Road ph. 7165721140 www.web	COMPANY LOGO	Page 3

### 2.) <u>Lateral Loads - Longitudinal Direction</u>:




- a) (-) signs signify wind lateral forces acting opposite to the direction of the arrows shown.
  b) Strength design values multiplied by 0.6 to obtain ASD values.
  c) Where the length of building (L) exceeds 4X the mean roof height (h), wind drag forces should additionally be considered.

	Wind Base Shear (ASD)						
	Load Case B: Longitudinal Direction						
Load Case	Load Case Walls (lbs) Gable Ends (lbs) Roof (lbs) Total Lateral Load (lbs) R <sub>A</sub> (lbs) R <sub>B</sub> (lbs)						
Positive Internal Pressure	752	489	0	1241	649	592	
Negative Internal Pressure	Negative Internal Pressure 752 489 0 1241 649 592						
Roof Pressure = 0	752	489	0	1241	649	592	
Min. Pressures (8 psf, 16 psf)	799	548	0	1347	673	673	

- a) Bottom half of wall neglected in tributary area calculations.
   b) Strength design values multiplied by 0.6 to obtain ASD values.

Wind Loads	Customer	Location		Job No. 2024D208
Norman J Abraham, P.E.	NJA Engineering	STRUCTURAL ENGINEERS	This report may not be copied, reproduced or distributed without the written consent of NJA Engineering	Rev.
5/18/2024	941 New Road ph. 7165721140 www.web	site.com	Copyright © 2024	Page 4

#### 3.) Roof Truss Reactions:



- a) Strength design values multiplied by 0.6 to obtain ASD values.
- b) Windward loads may be positive or negative depending on pitch of roof.

Roof Truss/Rafter Reactions (ASD)							
w/ Positive Internal Pressure							
Load Case	Horizontal Load (lbs)	Gross Uplift (lbs)	Net Uplift (lbs)	U <sub>1</sub> (lbs)	U <sub>2</sub> (lbs)		
Transverse Int. Zone	-63	48	-125	-86	-39		
Transverse End Zone	-81	54	-118	-90	-28		
Longitudinal Int. Zone	35	175	3	16	-13		
Longitudinal End Zone	60	265	92	71	21		

- a) Gross Uplift calculations do not include any counteracting roof dead loads.
- b) Net Uplift calculations include counteracting roof dead loads multiplied by 0.6 per load case (7) ASCE 7-10. c) Strength design values multiplied by 0.6 to obtain ASD values for wind loads. d) Loads based on truss spacing calculated at 16" o/c.

- e) Negative values for horizontal load indicate load acting in windward direction (tranverse load cases).
- f) Negative values for uplift indicate net downward force (zero uplift).

\*Disclaimer: The calculations produced herein are for initial design and estimating purposes only. The calculations and drawings presented do not constitute a fully engineered design. All of the potential load cases required to fully design an actual structure may not be provided by this calculator. For the design of an actual structure, a registered and licensed professional should be consulted as per IRC 2012 Sec. R802.10.2 and designed according to the minimum requirements of ASCE 7-10. The wind load calculations provided by this online tool are for educational and illustrative purposes only. Medeek Design assumes no liability or loss for any designs presented and does not guarantee fitness for use.

Subject Wind Loads	Customer	Location	Job No. 2024D208
Norman J Abraham, P.E.	NJA Engineering	This report may not be copied, reproduced o distributed without the structural ENGINEERS written consent of NJ written consent of NJ requirements.	-
5/18/2024	941 New Road ph. 7165721140 www.web	COMPANY LOGO	Page 5